



Serie EASY GAZ

FLEXIBLE 20/30/50Mts

DIMENSIÓN/DIMENSIONES									
DN	INCH	Ø INTERIOR INNER(MM)	Ø EXTERIOR OUTER(MM)	ESPESOR THICKNESS (MM)	MATERIAL	TOLERENCIA TOLERENCE	BAR A 20° C	RANGO TEMPERATURA RANGE TEMPERATURE	Nº ONDAS UNDULATION (50MM)
8	3/8"	8.8	13.2	0.2/0.25/0.3	AISI304	+/- 0.2 mm	16	-250°C + 600°C	13
12	1/2"	12.6	17.7	0.2/0.25/0.3	AISI304	+/- 0.2 mm	16	-250°C + 600°C	10
16	3/4"	15.8	20.9	0.2/0.25/0.3	AISI304	+/- 0.2 mm	16	-250°C + 600°C	10
20	1"	20.5	26.4	0.2/0.25/0.3	AISI304	+/- 0.2 mm	10	-250°C + 600°C	9
25	1 1/4"	26	32.2	0.2/0.25/0.3	AISI304	+/- 0.2 mm	10	-250°C + 600°C	10

FINO 20/30/50Mts

DIMENSIÓN/DIMENSIONES									
DN	INCH	Ø INTERIOR INNER(MM)	Ø EXTERIOR OUTER(MM)	ESPESOR THICKNESS (MM)	MATERIAL	TOLERENCIA TOLERENCE	BAR A 20° C	RANGO TEMPERATURA RANGE TEMPERATURE	Nº ONDAS UNDULATION (50MM)
8	3/8"	7.5	11.7	0.2/0.25/0.3	AISI304	+/- 0.2 mm	16	-250°C + 600°C	20
8_1	3/8"	9.2	12.9	0.2/0.25/0.3	AISI304	+/- 0.2 mm	16	-250°C + 600°C	18
12	1/2"	11.9	16.7	0.2/0.25/0.3	AISI304	+/- 0.2 mm	16	-250°C + 600°C	20
12_1	1/2"	12.2	17.4	0.2/0.25/0.3	AISI304	+/- 0.2 mm	16	-250°C + 600°C	15
16	3/4"	15.2	20.4	0.2/0.25/0.3	AISI304	+/- 0.2 mm	16	-250°C + 600°C	13
20	1"	19.6	26	0.2/0.25/0.3	AISI304	+/- 0.2 mm	10	-250°C + 600°C	17

Features

- 1. PVC corrugated hose in AISI 304.
- 2. Max.working pressure 10 to 16 Bar at 20° C (see tecnical sheet).
- 3. Temperature range -250°C + 600°C.
- 4. European Standard:UNE-EN ISO 15266.
- 5. Available 20/30/50Mts.

Caraterísticas

- 1. PVC tubo corrugado flexible AISI 304.
- 2. Alta presión de trabajo 10 o 16 Bar a 20° C (ver tabla).
- 3. Rango de temperatura -250°C + 600°C.
- 4. EU Norma:UNE-EN ISO 15266.
- 5. presentación en rollo 20/30/50Mts.

Aplication

- 1. Cold & Hot Water pipeline
- 2. Gas pipeline



Aplicación

- 1. Fría & Caliente agua hose
- 2. Gas hose

